

ASWMS

Manual Fork Over Stacker

Ideal and standard series for manual transport and lifting, with its different mast options and diverse lifting capacity enables to deal with a large number of applications in the warehouse or any other facilities.

- ◆ Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- ◆ We can offer additional protection for the operator through foot protection on the steering rollers.



- ◆ Safe parking with mechanical parking brake.
- ◆ Tiller pumping lifting and foot pedal lifting.



SPECIFICATIONS

MODEL			ASWMS1500				ASWMS2000	
FEATURE								
1.1	Capacity	Q kg	1500				2000	
1.2	Load Center	C mm	600				400	
DIMENSIONS								
2.1	Lifting height	h mm	3000				1600	
2.2	Mast lowered height	H mm	2020				2110	
2.3	Mast extend height	H1 mm	3510				2110	
2.4	Mast type		D				S	
2.5	Lowered height of fork	h1 mm	90				90	
2.6	Fixed fork outside distance	W mm	560				560	
2.7	Option adjustable fork, adjustable range	mm	330-870		330-680		330-870 330-680	
2.8	Fork length	sllel mm	1150				1150	
2.9	Overall width	W2 mm	870				780	
2.10	Overall length	L mm					1650	
2.11	Lifting speed	mm/time					≥16	
2.12	Lowering speed						Controllable	
2.13	Turing Radius	Wr mm	1590	1600	1600	1600	1590	
WHEEL								
3.1	wheel(drive/load) Type		PU/Nylon				PU/Nylon	
3.2	size of steering wheel	∅ D mm	∅ 180*50				∅ 180*50	
3.3	size of Loading wheel	∅ d mm	∅ 78*60				∅ 78*60	

